

L301 Color Label Printer

Ideal for Small Businesses

Creating professional labels on demand is easy with the L301. Bringing short-run label printing in-house saves time and money. Eliminate lead times, setup fees, plate changing fees, and order quantity minimums associated with outsourcing labels.

The L301's continuous roll printing capability allows businesses to print professional-quality labels as needed. **No more wasted time, wasted money, or wasted labels.**

Key Features

- ✓ Professional looking labels, on demand
- ✓ Simplify workflows and eliminate the hassles of sheet printing
- ✓ Flexibility to change label designs and content on the fly
- ✓ Minimize waste by printing only the labels you need
- ✓ Economically priced specifically for small businesses



Phone: 310.523.5800

Email: info@californialabel.com **Web:** californialabel.com



<u>AFINIA LABEĽ</u>

L301 Specifications

General:

Print Technology:	HP Thermal Inkjet
Print Resolutions:	Color: Up to 4800 x 1200 optimized dpi color; Black: Up to 1200 x 1200 rendered dpi
Print Speed:	Approximately 1.8 in/sec (46mm/sec) when printing a 2.2 inch-wide (56mm) image in draft mode
Size:	19"w x 21.5"d x 7"h (48.3cm x 54.6cm x 17.8cm)
Inks:	Black single pigment ink cartridge; Tri-color single dye ink cartridge
Media Types:	Compatible with wide range of paper, polyester, polypropylene, and vinyl label stocks. Supports gap, black mark, and continuous media
Media Sensing:	Auto calibration and auto detection of gap and black marks
Minimum Label Size:	1.75"w x 0.75"h (44.5mm x 19mm)
Maximum Label Size:	6"w* x 48"h (152mm* x 1219mm) - *Up to 8.5"w (216mm) with optional powered unwinder
Inter Label Gap Size:	0.125" – 0.3" (3mm x 8mm)
Black Mark Size:	0.125" – 0.3"
Label Thickness:	0.004" - 0.01"(0.1mm - 0.3mm)
Manual Cutter:	Included
Manual Unwinder:	Included, 6" max width, 6" OD (152mm)

Operating Environment:

Display:	Front panel touch screen
Operating Systems:	Windows 7, 8, and 10 (32 and 64 bit)
Data Interface:	USB 2.0 connection
Operating Temperature:	41 – 104°F (5 – 40°C)
Storage Temperature:	-40 – 140° F (-40 – 60°C)
Operating Humidity:	15 – 80% RH, 20 – 80% recommended
Non-operating Humidity:	10 – 90%
Warranty:	1-year



Label Printing Solutions for Every Level of Production

AfiniaLabel.com

Phone: 310.523.5800

Email: info@californialabel.com **Web:** californialabel.com

